THE RANGO CEMENTS LIMITED ALATHIYUR WORKS Excelence in Energy Management

Presenting members

Muthusamy P GM-Quality control



Radhakrishnan P V Sr. Manager-Process



Vengadesh S Manager-Process




The Ramco Cements Limited, Alathiyur Profile

A flagship company of RAMCO Group, having five Ceme manufacturing units, six grinding units and one packing u mortar and one ready mix unit with the total capacity of 1

Alathiyur plant was setup in two phases 1997 & 2001 with capacity of 3.05 Million Tons / Annum and 2 X 3700 TPE 2X18 + 6 MW - Coal based Thermal power plant

The manufacturing products are Ordinary Portland Cemer Pozzolana Cement and SRPC as per BIS & SLS standards


Ramco Sustainability Journey




IS/ISO 50001:2011 IS/ISO 9001: 2008 Quality Management System IS/ISO 14001: 2004 Environment Management System IS 18001: 2007 Occupational Health & Safety Management System

Energy Management System 5S Excellence Certified Company


Thermal energy Consumption



Electrical Specific Energy Consumption-Cement



Thermal energy Consumption




Electrical Specific Energy Consumption-OPC



Electrical Specific Energy Consumption-PPC



Electrical Specific Energy Consumption-Cement




Kwh / MT of Cement

11

OPC Contribution in Total Cement Production




Electrical Specific Energy Consumption up to Clinker




Global Norms/Standards



Road Map To Achieve Benchmark



Energy Conservation Projects Implemented in the years 2019-20, 2020-21& 2021-22



Energy Conservation Project 2019-20

S. No.	Energy Saving Project	Savings (Rs. Lacs)	Investments (Rs. Lacs)
1	Installation of VFD for Line-1 Preheater fan	5.58	12
2	Installation of VFD for Cement mill compressor	0.92	1
3	Heat resistant paint in preheater-2	1.58	0.2
4	Compressor air optimization in rawmill-1, coal mill-2	10.3	0
5	Blower air optimization in rawmill-1 and 2	6.6	0
6	Cement mill-1 unit bag filter optimization	1.8	0

Energy Conservation Project 2020-21

S. No.	Energy Saving Project	Savings (Rs. Lacs)	Investments (Rs. Lacs)
1	compressor optimization in Line-1 and 2	2.9	12
2	Unit bagfilter optimization in line-1 and line-2	0.9	1
3	Operating Mills and kiln in Advanced process control	8.6	0.2
4	Reduction in oxygen level from 4.2% to 3.8 %	2.9	0
5	Blowers optimization in Cementill-1	1.1	0


Energy Conservation Project 2021-22


S. No.	Energy Saving Project	Savings (Rs. Lacs)	Investments (Rs. Lacs)
1	Rawmill high efficiency fan retrofit with VFD drive	50.7	189
2	WHRS system in kiln-1 and 2	2800	108
3	Air cooled condensor for TPP	3248	105.8
4	Solar panel installation	135	92.5
5	Existing 89M3/ hr Boiler Feed pump vfd - ENERGY SAVINGS	69	38.88

Energy Conservation Projects

Year	No of Proposals	Investments- Rs Lacs	Savings-Rs Lacs
2019-20	6	132	99.5
2020-21	5	0	16.4
2021-22	5	534.2	6302

WHRS steam to TPP ejector eireuit









➢ Installed Cement Waste
 Heat Recovery (CWHR)
 Boílers with regenerative
 feed cycle in Line 1§ 2
 Clinker Cooler.

Reduction in coal consumption @ 30 TPD.

•Achieved Thermal energy


savings @ 330 kcal/kWh.

Waste Heat Recovery Boiler @ a cost of Rs.43 Crores ➢ Installed Cement Waste
 Heat Recovery (CWHR)
 Boílers with regenerative
 feed cycle in Line 1§ 2
 Clinker Cooler.

Reduction in coal consumption @ 30 TPD.

Achieved Thermal energy

savings @ 330 kcal/kWh.



We have Erected and

Commissioned 2 Nos. Waste

Heat Recovery Boilers (AQC

Boilers). We have earlier

installed Ejectors for ACC as

per the design steam output


pressure from AQC Boilers @

25-29 Kg/cm2 and

C.

Temperature of 370-390 Deg

Accordingly, we have designed and installed steam pipeline to take 0.3 TPH of steam to each Air cooled condenser Ejector @ 25 Kg/cm2 pressure




During normal running of WHR Boilers, we are unable to get constant designed steam pressure of 25 Kg/cm2 due to various Kiln operating conditions. The AQC Boiler steam pressure


is varying from 9 Kg/cm2

to 30 Kg/cm2.

Due to this steam pressure fluctuation, we are unable to utilize the WHR Boiler steam continuously for Air cooled condenser Ejectors. To overcome 🛸 this issue, we propose to change Ejector nozzles so as to operate ACC Ejectors at minimum pressure of 9 Kg/cm2.



Innovative Project -1




Froath floatation

Recovery of Limestone from Reject Material by Floatation Plant @ Cost of <u>Rs.63 Crores</u>



- Achieved 20% Recovery of Limestone from reject
- 80% of Reject material used for Backfilling of Mine Pits

In our Alathiyur mines we are having very low grade límestone (with sílíca of 18 -25%) 68 Lakhs Tones which is 🌑 26% in total reserves and very Very low grade (25-33% sílíca) 52 Lakhs Tones which is 20% in total reserves which is not usable directly for cement



•We have installed Beneficiation / washing


plant in year 2014 for

consuming 18-25% sílica

líme stone for Clínker

production after washing.

•In the existing Limestone Beneficiation plant, we are able to recover 55-56% of cement grade limestone with silica range of 14-16% and LSF range between 100-110.




•Out of the Balance rejected material, 32% of the material is being rejected as slurry with 60% moisture and 12% of the material is rejected as sand (-2 mm).

•The slurry contains very fine particle of less than 300 microns and almost 75% of the @== = particles are less than 25 mícrons.

•Due to smaller particles, drying of slurry is very difficult task and it took more than a month to reduce the moisture level from 60% to 35 %

•The basic principle is to change the mineral element surface properties of hydrophobic (water repellent) and hydrophilic by adding some Reagents.



If a mixture of hydrophobic and hydrophilic particles are suspended in water and air is bubbled through the suspension, then the hydrophobic particles will tend to attach to the air bubbles and float to the surface and hydrophilic particles are settled down as tailings.


To process the slurry from límestone benefication plant and recover cement grade

límestone from waste ..

The slurry generated in

benefication plant is feed to the

froath floatation cells.



•6 banks of cells is present

in the froath floatation

process.

•Sodium hydroxide, sodium silicate and sodium oleate is used in the respective cell for seperation of silica and CaO from slurry.

Renewable Energy

	2019-20		2020-21		2021-22	
Type of RES	Energy	Annual	Energy	Annual	Energy	Annual
Type of KES	Generated	Savings	Generated	Savings	Generated	Savings
	(kWh)	(Rs.)	(kWh)	(Rs.)	(kWh)	(Rs.)
Solar photovoltaic	52924	224927	51092	201813	480000	2880000

Total installed capacity during the year 1996 is 33.235 MW, which was the SINGLE LARGEST WIND FARM IN THE SOUTH EAST ASIA at that time.

The wind mill capacity is constantly upgraded and now at present the **capacity is** 166 MW with 229 individual Wind Electric Generators. The unit generation is 268.7 Million KWh for 2021-22

Utilization of waste material as fuel

S. No	Type of Waste Fuel used	Quantity of waste fuel used (MT)	Equivalent of Conventional energy used (Ton of coal)	Waste fuel as % of total energy
1	AFR Liquid	794.81	189	0.2%
2	AFR Solid	3583.3	896	0.7%
3	Lignite Unburn (Pond Ash)	5368	1764	1.4%
4	TPP Reject	7225.5	1498	1.2%
5	Ambika Reject	538	61	0.05%
6	AFR Liquid Mix Spent	394.53	27	0.02%
		3.59%		

Utilization of waste material as Raw material

S. No	Name of Alternative	Name of material	Quantity used (MT/ Year)					
5. NU	raw material	gets replaced	2019-20	2020-21	2021-22			
1	slag	Iron ore	117704	79734	82379			
2	Chemical sludge	Limestone	1003	675	1166			

GHG Inventorisation

Year en CO ₂		pe 1 sions (MT)/T hent	Scope 2 emissions CO ₂ e (MT)/T Cement	Scope 3 emissions CO ₂ e (MT)/T Cement	Total CO₂e (MT)/T Cement	% Reduction in emission		
2019-20		68	-390	15.00	693.2			
2020-21	901		-217	12.10	696			
2021-22	903.9		-225	12.10	691			
Scope 1 emis	sions	Calcination, Fuel for kiln & CBPP, owned vehicle, Refrigeration & AC						
Scope 2 emis	ssions	Power consumption						
Scope 3 emis	ssions	Raw Material Supply & Product delivery						

Yes, We have a integrated green purchase policy to ensure the Conservation of Energy for sustaínable development, Adopting the state of art technology, energy efficient procurement and practices, Life cycle cost assement of equipment's and encouraging team efforts.



Projects:

Procurement of high efficiency

fan ín rawmíll-1, Rawmíll -2

classífier fan.

AQC steam optimization

AQC steam to ejector circuit

Energy Reporting Format



L1 L2 L1 L2 L1 L2 LSS Image: Sub tool of the sub to														
L1 L2 L1 L2 L1 L2 LSS I <						_	Line1			Line2	1	Fo	r L1 and L	2
LSS Crushei Crushei Mines Sub tot Raw mill Raw mill Raw mill Coal mill	eter		кwн		ĸw	Kwh/ Matl	Kwh/ Clinker	Kwh/ Cement	Kwh/ Matl	Kwh/ Clinker	Kwh/ Cement	Kwh/ Mati	Kwh/ Clinker	Kwh Ceme
LSS Crushes Mines Raw mill Raw Mi Raw Mil Raw Mi Raw Mi Raw Mi Raw Mi Raw Mi Raw Mi Raw Mi Raw Mi Raw Mi Coal Mi Coa		L1	L2	L1	L2									
LSS Mines Raw mill Raw Mines Coal mill Coal mill Coal mill ElE-K1. ELE-K1. ELE-K1. Sub t	er Main Motor													
Raw mill Raw mill Raw mill Raw mill Raw Mil Raw Mi Raw M Raw Mi Raw M Raw R	er Auxiliaries													
Raw mill Raw Mil Raw Mi Raw M														
Raw mill Raw Mil RM.RMM Coal mill Coal Mil Coal M														
Raw mill RM,RMF Sub toi Coal Mil Coal mill Coal Mill Coal mill Coal Mill Coal mill Coal mill Kiln ELE-K1- Kiln ELE-K1- ELE-K1- ELE-K1-	ill Main Motor					_								L
Coal mill Coal mill Coal mill Coal mil			_	L		_								<u> </u>
Coal mill Coal m														
Coal mill Coal mill Coal mill Coal mil Coal mil Coal mil Coal mil Coal mi Coal			_	L		_	-			-	-			<u> </u>
Coal mill Coal Mill Coal mill Coal Mill Coal coal coal coal coal coal coal and coal coal coal coal coal mill Coal mill Kiln ELE-K1- ELE-K1- ELE-K1- Booster A/C and Cement Sub too Bulker ELE-K1- Bulker ELE-K1- Bulker ELE-K1- Packing plant Pumpt Service Pumpt <td< td=""><td></td><td></td><td>_</td><td></td><td></td><td>_</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td><u> </u></td></td<>			_			_								<u> </u>
Coal mill Coal Hai Coal mill Coal Can Sub tot Sub tot Sub tot ELE-K1- ELE-K1- ELE-K1- Boospatch Cement Sub too Sub too Despatch Packing Packing plant Packing Service Planp Packing plant Cement Cator for Equiv Clinker			_			_								
Kiln Coal crr. Sub tot Kiln ELE-K1. ELE			-			-								
Kiin Sub tot Kiin ELE-K1. ELE-K1. Colorer I. Colorer I. KWh / M. Vithout Ele-K1. Booster Ele-K1. Buiker Booster Buiker Ele-K1. Buiker Ele-K1. Buiker Pumpt Service Image: Plane I. Total Image: Plane I. Facking plant Image: Plane I. Factor for Equiv Clinker Cau MilL Image: Plane I. Could HER Image: Plane I.					1	-	1			1	1			I
Kiin ELE-K1. ELE						-								<u> </u>
Kiln ELE-K1. ELE			-		1	-					1			<u> </u>
Kiln ELE-K1. ELE-K1. ELE-K1. ELE-K1. Cooler f Kiln & K Service Tr.Los: A/C and Clinkerisation Up to clinkerisation KWh / M Cement mill Cement Booster Fly Ash Cement Booster Despatch without Bulker Cement Booster Fly Ash Cement Sub tol Despatch without Bulker Packing Packing plant Service Packing Packing plant Service Packing Packing plant Factor for Equiv Clinker Cement Cement Clinker Cement Pumpi Clinker Cement Clinker L1 L2 For LI & L2 LIGHITIN PUMPH RAWMILL COALMILL CCR AC				<u> </u>	1	-				1	1			<u> </u>
Kiln ELE-K1. ELE-K1. Cooler f Kiln & K Sub To Service Tr.Los Up to clinkerisation KWh / M Cement clinkerisation Cament Cement Buiker Despatch without Buiker Buiker Buiker Cament Cement Sub tor Despatch without Buiker Buiker Packing Packing plant Service Packing Packing plant Causer Cement Cement Causer Causer Cotor for Equit Clinker Causer Clinker Causer Pump I Causer Pump I Causer Pump I Causer Pump I Causer Causer Causer Pump I Color for Equit Clinker Causer Pump I Causer Pump I Causer Causer	-B.H.MCC				1	-			l	1	1			t
Kiin ELE-K1. Cooler f Kiin & K Sub To Service Tr.Los Up to clinkerisation KWM / M Cement mill Cement Booster Fly Ash Cement Sub to Despatch without Bulker Sub to Despatch without Bulker Packing Fly Ash Cement Sub to Packing plant Packing Fly Ash Cement Service Packing Fly Ash Cement Service Packing Fly Ash Cement L1 L2 L1 L2 CAMILL CCR AC	-C.F.MCC				<u> </u>						1			
Service Cement mill Conternation of the service Cement mill Cement Sub tor Sub	-D.C.Drive													<u> </u>
Service Kill & K Sub To Up to clinkerisation Tr.Los Cement mill KWh / M Cement mill Cement Booster Fly Ash Cement Bulker Despatch without Bulker Packing Plant Despatch Packing Plant Service Packing Plant Total Tr.Los L1 L2 For L1 & L2 For L1 & L2 CRUSHER PUMP H RAWMILL	Fan & C'ker Trans													
Service Service Service Up to clinkerisation KWh /M Cement Clinkerisation KWh /M Cement Cement mill Cement Booster Fly Ash Cement Sub tol Despatch without Bulker Sub tol Despatch Without Bulker Packing Packing plant Service Packing Packing plant Total Total Factor for Equiv Clinker Clinker Cement Cement Clinker Cement Cement Color Pump I Color Cinker Cause Pump I Color Cinker Color Cinker Color Cinker Cause Pump I Color Cinker Color Pump I Color Cause Color Cause	Kiln Feed MCC													
Service A/C and Up to Clinkerisation KWh / M Clinkerisation KWh / M Cement Cement Cement Booster Fly Ash Cement Despatch without Bulker Sub tot Despatch Without Bulker Packing Packing plant Service Packing Packing plant Service Packing Pumpi Total TOTAL Factor for Equiv Clinker Clinker Cement Clinker Clinker Cult L1 L1 L2 For LI & L2 LIGHITIN CAUMILL CCR AC COALMILL LOSSES														
Up to clinkerisation kWh / M Cement mill Cement Cement mill Cement Despatch without Bulker Bulker Despatch Packing plant Clinker Cement Total Clinker Cement Clk Cem L1 L2 L1 L2 For L1 & L2 HUMPH CRUSHER PUMP H CALMILL COALMILL COSSES	ss,Lighting, CCR d Pump House													
Cement mill Cement mill Cement mill Cement Cement Cement Cement Cement Cement Cement Cement Sub tor Su	MT of clinker													
Cement mill Cement mill Despatch Without Bulker Despatch Packing plant Factor for Equiv Clinker L1 L2 L1 L2 For L1 &L2 For L1 &L2 UGHTTI CRUSHER RAWMILL COALMILL EDU EDU EDU EDU EDU EDU EDU E	t Mill Main drive													
Cement mill Cement mill Despatch without Bulker Despatch Packing plant Factor for Equiv Clinker L1 L2 L1 L2 For L1 L2 L0HTIN CRUSHER RAWMILL COALMILL E C C C C C C C C C C C C	t Mill Ean		-			-								<u> </u>
Buiker Fly Ash Cement Buiker Sub tot Buiker Packing plant Packing plant Packing Pump I Total TotAL Factor for Equin Clinker CRUSHER PUMP I RAWMILL COALMILL														
Despatch without Bulker Cement Sub tot Despatch Image: Constraint of the system Bulker Image: Constraint of the system Packing plant Image: Constraint of the system Packing plant Packing plant Image: Constraint of the system Packing plant Image: Constraint of the system Packing plant Image: Constraint of the system Packing plant Factor for Equiv Clinker Cement Clk CRUSHER Image: Constraint of the system RAWMILL Image: Constraint of the system Constraint of the system						-								
Despatch without Bulker Bulker Bulker Despatch Packing plant Total Total Clinker Clink	t Mill Auxiliaries													
Despatch without Bulker Bulker Despatch Packing plant Service Total CRUSHER L1 L2 L1 L2 For L1 & L2 For L1 & L2 For L1 & L2 For L1 & L2 COALMILL L LSSEE														<u> </u>
Without Bulker Packing Bulker Packing Bulker Packing Bulker Packing Bulker Packing Service Pump i Total TOTAL Factor for Equiv Clinker CRUSHER L1 RAWMILL COALMILL														
Bulker Packing plant Packing plant Packing plant Packing plant Packing plant Service TriLos Pump i Total TOTAL TOTAL Factor for Equiv Clinker Cement Clk CRUSHER I L1 L2 For L1 & L2 RAWMILL COALMILL COSES CLOSES														1
Despatch Packing Packing plant Packing Service Tr.Los Purpling Purpling Total TOTAL Factor for Equiv Clinker Cement Clk CRUSHER CRUSHER RAWMILL CCRAC COALMILL L1														
Packing plant Packing Service Tr.Loss Total Total Factor for Equin Clinker CRUSHER It RAWMILL COALMILL														
Service Tr.Los: Pump I Total TOTAL Factor for Equin Clinker L1 L2 L1 L2 Factor for Equin Clinker CRUSHER PUMP H RAWMILL CCR AG COALMILL L0								_						
Service Pump I Total TOTAL Factor for Equiv Clinker L1 L2 L1 L2 CRUSHER CRUSHER RAWMILL CRCRAC COALMILL CRCRAC					I					I	I			
Total Pump i Factor for Equiv Clinker Cement Clk Cem L1 L2 L1 L2 For L1 & L2 LIGHITIN CRUSHER PUMP H CCR AG CCR AG RAWMILL CCR AG CCR AG	s,Lighting and				1					1	1			1
Clinker Cement Clk Cem L1 L2 L1 L2 For L1 & L2 LIGHTTIN CRUSHER PUMP H CCR AG CCR AG CCR AG CCR AG Advector COALMILL CCR AG LOSSES LOSSES COSSES										I				I
L1 L2 L1 L2 For L1 & L2 LIGHTIN CRUSHER CRUSHER CCRAC RAWMILL CCRAC COALMILL LOSSES	_				I		L		0		4			I
CRUSHER PUMP H RAWMILL CCR AC COALMILL LOSSES		VICE U	UNITS						On Date	Mon Date				
RAWMILL CCR AC COALMILL LOSSES							Clk Proc Cem Pro			1	Cooler	/ent Fan-1	KW	I
COALMILL LOSSES						1	Desp	.				/ent Fan-1 /ent Fan-2		1
						-	P. Comb				Cooler			1
KILN TOTAL						-			I	I	I			<u> </u>
	-						Line-1		L	I	L			
							Line-2				I			
Energy Manager		G	M –E&I									۵\/۵	P-Works	:
Lifer by manager		U											VV OT KS	,

Involvement of Employees in ENCON

Energy management cell : 7 Teams

Thermal Energy audit : Heat balance in Pyro section-Preheater, Kiln, Cooler & False Air study.

Electrical Energy audit : Efficiency of Motors, Fans, Blowers, Compressors etc.,

Quality circle forum : 10 Quality teams

5S & Suggestion scheme implemented

Green Product and ISO 50001




Other Innovative technologies implemented

Advance process control - Fuzzy logic for improving Producti reduction in stoppages in the optimization of raw mill, coal cement mill in advance process control mechanism to elimin intervention to reduce fossil fuel and electrical energy.

The prediction model such as regression model and Neural has been used to predict the result before and optimize the operating parameters.

The mills has been optimized with continuous monitoring of logic programme to optimize the production with low specificonsumption.



Long Term Vision on EE

The long term target on electrical efficiency is 65 Kwh per to and reduce the specific heat consumption to 686 Kcal per kg


The support required to meet the target is achieved by mean Technical team along with Financial allotment. Our manager having keen interest for implementing all energy conserving proposals.

To achieve this target the proposal are-1.WHRS system 2.Compressors and blowers optimization 3.Mills and kilns optimization by Fuzzy logic

Air Cooled Condenser for 2X18 MW Captive Thermal Power Plant at a Cost Of Rs.40 Crs

Achieved Raw water consumption Reduction by 92% (3843 KLD to 353 KLD) and effluent Generation Reduction i.e., 883 KLD to 97 KLD.

CPP Water Consumption trend in KLD



Page 46

Procured Battery Car for Site rounds

Procured CNG vehicle for Water Tanker usage @ 20 Lakhs

RAMCO CEMENT

Bio-Diesel consumed Qty (2021) : 3,15,000 Liters

Procured Electric vehicle for

Internal material transfer

uuuuuuu

Usage of Bio-Diesel for Factory Auto

ECOMMUTE DAY EVERY WEDNESDAY



AFR Shredder, Storage Shed & Feeding system-35 crores



IE DAY EVERY WEDNESDAY



National Level Energy Awards





Afforestation in Mines, Factory and surroundings



Mines Name	North Mines	South Mines	Tular Mines	South of South Mines	Total
Number of Saplings Planted since 2010	47,314	95,691	89,741	32,477	2,65,223

We have donated 1000 saplings to Adhanakurichi (600), Alathiyur (250) and Manakkudayan (150) panchayat to plant in the panchayat vacant lands.



С

В



Bio Gas Plant in colont and factory

Fuel Saved : 12-15 Kg LPG/day

Bio Gas Plant	At Factory Canteen	At Colony / Bachelor Mess
Capacity (Food waste)	150 Kg/Day	150 Kg/Day
Cumulative Feed per year	28 Tons	14.6 Tons
Bio Gas Generation per year(M3)	2753	1460
PG cylinders savings per year	72.4	38.4

Rain Water Harvesting Pond and Bird Sanctuary



Bio Composting Vermi Composting



Environment Projects 2020-22 @ a cost of 190.58 Crores

No	Project	Project Cost	Impact
1	Raw Mill Secondary Classifier Project	39.00 Cr	Resource conservation
2	Air Cooled Condenser for 2X18 MW Captive Thermal Power Plant	40.00 Cr	Water Conservation
3	Recovery of Limestone & Water from Tailings by Floatation Plant	63.00 Cr	Resource conservation
4	Solar Plant Installation – 290 KWp	1.35 Cr	Renewable Energy usage
5	Line 1 Preheater fan MV VFD installation	1.08 Cr	Energy Conservation
6	Line-1 Cement Mill bag house bag replacement to reduce SPM<10 mg/Nm3	0.56 Cr	Prevention of Pollution
7	Bag Cleaning Device in 4th Packer	0 14 Cr	Prevention of Pollution
8	Mines Additional Base Road Formation	1 15 Cr	Prevention of Pollution
9	Procured CNG vehicle for Water Tanker usage	0.20 Cr	Prevention of Pollution
10	Segregation Shed for Solid Waste	0.13 Cr	Prevention of Pollution
11	Waste Heat Recovery Boiler (Air Quenching Chamber)	43.00 Cr	Energy Conservation
12	Boiler Feed Water Pump VFD Installation	0.52 Cr	Energy Conservation
13	Upgraded Online Stack PM Emission Monitors	0.40 Cr	Env Monitoring



THE RANGO GEMENTS LIMITED MATHIMUR WORKS

Thank you